



## 2007 IEMCA VIP 65E II Bar Feeder



**BAR SIZE CAP.:** 5MM - 65MM

**BAR LENGTH CAP.:** LATHE SPINDLE LENGTH

**MAX / MIN BAR LENGTH:** 63.5" / 8.3"

**MAGAZINE CAP.:** 29 LINEAR INCHES

**BAR PUSHER 1:** 12MM FOR .5" TO 1" DIA. BAR

**FEEDING SPEED:** 20"/sec MAX. (ADJUSTABLE)

**BAR CHANGE TIME:** 28 SECONDS FOR 48" BAR

**WEIGHT:** 1,600 LBS

CUSTOM ELECTRICAL CABLE PACKAGE & INTERFACE KIT

**BAR PUSHER 2:** 21MM FOR 1" TO 3.125" DIA. BAR

**OPERATING VOLTAGE:** 230V AC 3 PHASE (400V AVAIL.)

**CONTROL VOLTAGE:** 24 VOLTS DC

**TOTAL POWER REQUIRED:** 1.875 kVA/1.5kW

**COMPRESSED AIR REQUIREMENT:** 90 PSI, 10 cfm

**FACING ACCURACY:** +/- .020"

**BAR STRAIGHTNESS:** REQUIRED FOR INDUSTRY STD.

**COLOR:** RAL 5002 BLUE, RAL 7035 LIGHT GRAY

AXIAL DISPLACEMENT TRACK Z AXIS

This list is subject to change without notice.

This specification sheet is confidential and is just a guide. Although obtained from sources deemed reliable, Premier Equipment makes no warranty or guarantee as to the accuracy of the information herein contained. It is the purchaser's responsibility to verify specifications.

PREMIER EQUIPMENT 29225 CHAGRIN BLVD, SUITE 250 BEACHWOOD, OH 44122

[www.buyprimerequipment.com](http://www.buyprimerequipment.com)

Ph: (216) 593-7000 Fax: (216) 593-0557 Toll-free (888) 897-1197